


Code	PB94C-BLK		
Standard	EN ISO 20345:2011 S3 HRO HI CI SRC		
Name / Description	Ankle Length Welders Boot		
Weight	750 grams		
Colour	Black	<i>*Available in sizes 6.5 and 10.5</i>	


Sizes	3	4	5	6*	7	8	9	10*	11	12	13		
-------	---	---	---	----	---	---	---	-----	----	----	----	--	--

Properties	<p>Upper: Full Grain Barton Print Buffalo Leather with Special Heat Resistant properties. (Leather 1.8-2.0mm)</p> <p>Inner Lining: Moisture Wicking Textile to Vamp only.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Textile Puncture Resistant Protective Midsole – Min. 1100N.</p> <p>Sole Unit: Dual Density Rubber/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p> <p>Additional Features: Para Aramid Flame resistant stitching, Velcro Quick Release Fastening.</p>
------------	---

Areas of Application	<p>The PB94C is suitable for use in welding environments where there is a high risk of it coming into contact with hot sparks. Made using only full grain leather, Para Aramid stitching and a textile lining, this product is highly flame resistant and can be used for a variety of welding applications. Overcap protects leather from wearing away when kneeling.</p>
----------------------	--

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	<p>S3 HRO HI CI SRC</p>	 <p>PRODUCT PERFORMANCE PASSION</p>	
----------	--	---------------------------------	---	--

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk </p>
---------	---