## 111







**PLANET HAUT BLEU S3S** 






New standard 2022: Standard EN ISO 20345: 2022

# TRAINER LSG

Also available with the quick lacing NBS System









Ref. PLAHS3SBE

#### **Product Highlights**

- Polyester upper made from recycled PET bottles: lightness, breathability, tear and abrasion resistance.
- Bamboo fiber and recycled polyester lining: antiallergic and anti-microbial, thermoregulatory effect.
- Memory Foam by Lemaitre antibacterial insole with memory foam, recycled, antibacterial, shape memory, energy absorption and dissipation, MSD prevention.
- Outsole injected with recycled polyol from our production waste.
- Timeless sneaker style
- Eco-designed safety shoe made from recycled materials and components > 25% recycled or reused materials (ISO 14021: 2016 standard).





7





# CARBON single-density antistatic sole

- Developed outsole for industrial and urban floors: good adherence
- Sole tested and certified to the additional requirement of slip resistance as per SR in the new standard 20345:2022
- Large surface support: optimum stability
- Shock absorption: preservation of the back and joints
- Notches for enhanced grip
- Flexibility and lightness: sole that facilitates walking

#### USE

- Service company, crafts, management
- Logistics, services, handling, distribution, transport
- Public authorities and administrations





### **PLANET HAUT BLEU S3S**













New standard 2022: Standard EN ISO 20345:2022

#### **Characteristics of the upper**

- Upper material: water-repellent velvet effect microfiber and 90% recycled PET fabric
- Tongue: water-repellent microfiber and 90% recycled PET fabric
- Lining: 61% recycled materials (bambou & recycled polyester)
- Laces: 100% recycled

#### Charactericts of the sole

- Designation: CARBON PU2D
- Material: polyurethane with recycled polyol
- Antistatic sole
- Adhesion coefficient (fundamental requirements): forward heel slip: 0,55 (standard ≥ 0,31) backward forepart slip: 0,71 (standard ≥ 0,36)
- SR Adhesion coefficient: forward heel slip: 0,25 (standard ≥ 0,19) backward forepart slip: 0,30 (standard ≥ 0,22)

#### VARIANT



#### Practical information

Weight of one shoe size 42: 489 g

AET n° 0075/007/161/02/23/0176 EXT 03/05/23

#### **Packaging**

Size 35 to 42			Size 43 to 50		
<b>shoebox</b> 315 x 220 x 123 mm		n	shoel	<b>50x</b> 355 x 220 x 130 mm	
<b>carton</b> 635 x 445 x 315 mm			<b>carton</b> 660 x 450 x 360 mm		
10 shoeboxes per carton			10 shoeboxes per carton		
Genc	ods				
35	3237154521359		43	3237154521434	
36	3237154521366		44	3237154521441	
37	3237154521373		45	3237154521458	
38	3237154521380		46	3237154521465	
39	3237154521397	1	47	3237154521472	
40	3237154521403		48	3237154521489	

49

50

#### Memo for basic and additional requirements of the standard EN ISO 20345:2022

#### Safety Footwear



Sliding test



**Fundamental requirements** 

lauryl sulfate (NaLS).













41

42



Shock absorption at

Fuel oil-resistant outsole



3237154521410

3237154521427

Insulation against cold

3237154521496

3237154521502



Insulation against heat



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Abrasion resistant scuff cap



Ladder grip system



Marking Slip-resistant shoe on a tiled floor with a solution of sodium

Shoe resistant to slipping on a tiled floor with glycerin.



200 J toe cap: Protection of the forefoot against



Non-metallic puncture-resistant midsole resistant with a 3 mm point (type PS)



Electrostatic discharge



Ankle protection

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024 F - 67350 Val de Moder Tél. +33 (0)3 88 72 28 80



Safety since 1974

Member of SYNAMAP



DON\_LS 04 TDS 0122

update: 27/10/23

