





|                    |  |   |
|--------------------|--|---|
| <b>Name</b>        | G19-BLU  |  |
| <b>Standard</b>    | EN388:2016 4.2.4.4.X                                   |   |
| <b>Description</b> | Perf Superior FR Aramid Welding Gauntlet SAF037 (35cm) |   |
| <b>Packaging</b>   | 10 Pair Pack. 60 Pair Carton.                          |   |
| <b>Colour</b>      | Blue   |   |

|              |    |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--------------|----|--|--|--|--|--|--|--|--|--|--|--|--|--|
| <b>Sizes</b> | 10 |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--------------|----|--|--|--|--|--|--|--|--|--|--|--|--|--|

|                   |  |
|-------------------|--|
| <b>Properties</b> | <p><b>Material</b> – Top Quality Shoulder Split Leather.</p> <p><b>Inner Lining</b> – Cotton.</p> <p><b>Additional Features</b> – Reinforced Grip on Palm. Cut + Flame Resistant Kevlar Stitching. Welted Seams.</p> |
|-------------------|--|

|                             |   |
|-----------------------------|---|
| <b>Areas of Application</b> | <p>Gas Welding + Fabrication.</p> <p>Approved to BSEN 12477 Type A BSEN407:2004 4.2.3.X.4.X</p> |
|-----------------------------|---|

|                 |   |  |  |          |                            |          |                       |          |                        |          |                            |   |
|-----------------|---|--|--|----------|----------------------------|----------|-----------------------|----------|------------------------|----------|----------------------------|---|
| <b>Standard</b> | <p>EN 420</p>  <p>Cat. 2</p> | <p>EN 388</p>  <p>4A 2B 4C 4D</p> | <table border="1"> <tr> <td><b>A</b></td> <td><b>Abrasion Resistance</b></td> </tr> <tr> <td><b>B</b></td> <td><b>Cut Resistance</b></td> </tr> <tr> <td><b>C</b></td> <td><b>Tear Resistance</b></td> </tr> <tr> <td><b>D</b></td> <td><b>Puncture Resistance</b></td> </tr> </table> | <b>A</b> | <b>Abrasion Resistance</b> | <b>B</b> | <b>Cut Resistance</b> | <b>C</b> | <b>Tear Resistance</b> | <b>D</b> | <b>Puncture Resistance</b> |  <p><b>PERF</b></p> <p>PRODUCT PERFORMANCE PASSION</p> |
| <b>A</b>        | <b>Abrasion Resistance</b>  |  |  |          |                            |          |                       |          |                        |          |                            |   |
| <b>B</b>        | <b>Cut Resistance</b>   |  |  |          |                            |          |                       |          |                        |          |                            |   |
| <b>C</b>        | <b>Tear Resistance</b>  |  |  |          |                            |          |                       |          |                        |          |                            |   |
| <b>D</b>        | <b>Puncture Resistance</b>  |  |  |          |                            |          |                       |          |                        |          |                            |   |

|                    |   |
|--------------------|---|
| <b>Limitations</b> | <p>This glove does not protect from chemical, bacteriological, electrostatic and thermic hazards. Do not use when working with rotating parts. <b>Used gloves with obvious damage do not offer any protection and must be replaced.</b></p> |
|--------------------|---|

|                |  |
|----------------|--|
| <b>Symbols</b> |  |
|----------------|--|

|                |   |
|----------------|---|
| <b>Contact</b> | <p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP<br/>   <a href="mailto:sales@performance-brands.co.uk">sales@performance-brands.co.uk</a>   <a href="http://www.performance-brands.co.uk">www.performance-brands.co.uk</a>  </p> |
|----------------|---|