

Code	H6 E	N166 1 B KN	
Standard	EN397:2012 + A1:2012 / EN166 CLASS 1		
Name / Description	Hydro-Shield Safety Helmet		
Packaging	4 per carton		
Colours	Black, White		
Sizes	One Size, 53 – 64cm.		
Properties	<ul> <li>Shell manufactured from high impact ABS</li> <li>Hi-Performance, CE - EN397 2012 Certified</li> <li>Internal retractable visor – EN166 Class 1 Optical</li> <li>Anti scratch (K)</li> <li>Anti Fog (N)</li> <li>Impact (B) – small object travelling at 120 meters per second</li> <li>High tensile strength 25mm terylene webbing</li> <li>Three layer highly absorbent sweatband with embedded foam</li> <li>Withstands temperatures down to -20°C</li> <li>Artificial ageing (durability up to 5 years)</li> </ul>		
Areas of Application	The Hydro Shield is suitable for use in a variety of industrial applications.  Typical applications are construction and general industry.		
Standard	EN 397:2012 + A1:2012 / EN166 CLASS 1	7E7F	
Care Instructions	Clean with a damp cloth. If helmet is damaged it will not offer full protection and must be replaced.		
Symbols			
Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP   sales@performance-brands.co.uk   www.performance-brands.co.uk		