

Code	PB111-BLK														
Standard	EN ISO 20345:2011 S3 SRC ESD									D			5		
Name / Description	Endurance Low – ESD Safety Trainer													and a start the	
Weight	550 grams														
Colour	Black														
Sizes	6	7	8	9	10	11	12								
Properties	2.2m Inne Toe Mids Sole Prop Resi Foot	 Upper: Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.2mm). Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Fibreglass Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Lightweight Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. Special Features: Abrasion Resistant Material across Toe, Vamp and Heel. 													
Areas of Application	The Endurance Low is suitable for any environments that specify an ESD requirement. Typical applications include electronic manufacturing, car production, chemical sites and pharmaceuticals. The extra protection across the toe area makes it perfect for jobs which involve kneeling as the leather is prevented from being worn away from the toe.														
Standard	EN ISO 20345:2011 C C C S3 SRC ESD Cat. 2														
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.														
Symbols															
Contact	Performance Brands Ltd The Pavilion, Bowcliffe Hall, Bramham, Wetherby. LS23 6LP <u>sales@performance-brands.co.uk</u> <u>www.performance-brands.co.uk</u>														