

Name	PB 15	
Standard	EN ISO 20345:2011 S3 HRO HI CI SRC	
Description	Black Dual Density Rubber Safety Boot	
Weight	920 grams	
Colour	Black	

Sizes	5	6	7	8	9	10	11	12	13				
-------	---	---	---	---	---	----	----	----	----	--	--	--	--

Properties	<p><b>Upper</b> – Breathable, Full Grain Leather with Leather Tongue and Collar. (Leather 1.8-2.2mm)</p> <p><b>Inner Lining</b> – Abrasion Resistant, Moisture Wicking Textile.</p> <p><b>Toe Cap</b> – Steel Toe Cap Resistant to 200J.</p> <p><b>Midsole</b> – Stainless Steel Midsole – Min. 1100N.</p> <p><b>Sole Unit</b> – Dual Density Rubber/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p><b>Footbed</b> – Moisture Wicking, Breathable, and Washable Footbed.</p>
------------	--

Areas of Application	The PB 15 is suitable for most heavy duty applications. Typical applications include digging, groundworks, construction, engineering, utilities, and rail.
----------------------	--

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	<p>S3 HRO HI CI SRC</p>	 <p>PRODUCT PERFORMANCE PASSION</p>	
----------	--	---------------------------------	---	--

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	---

Symbols	
---------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP   <a href="mailto:sales@performance-brands.co.uk">sales@performance-brands.co.uk</a>   <a href="http://www.performance-brands.co.uk">www.performance-brands.co.uk</a>
---------	--