

Name	PB 202 Libertine High					•	4		
Standard	EN ISO 20345:2011 S3 SRC					OLEN	AAITRE and April 171		
Description	Black S3 Ladies Safety Boot					Sector Sector			
Weight	400 grams		in a second s	M					
Colour	Black								R
Sizes	3 4	5 6	7 8						
Properties	<ul> <li>Upper – Breathable, Full Grain Super Soft Tumbled Leather.</li> <li>Inner Lining – Abrasion Resistant, Moisture Wicking Textile.</li> <li>Toe Cap – Polycarbonate Toe Cap Resistant to 200J.</li> <li>Midsole – Textile Pierce Resistant Midsole – Min. 1100N.</li> <li>Sole Unit – Lightweight Dual Density Parabolic PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance.</li> <li>Footbed – Moisture Wicking, Breathable, and Washable Footbed.</li> </ul>								
Areas of Application	The Libertine High is suitable for most industrial applications. Typical applications include construction, warehousing, manufacturing and distribution. The textile midsole makes the boot ideal for driving as the boot is very lightweight and flexible.								
Standard	EN ISO 20345:2011 <b>C E</b> Cat. 2	S3 SRC	LEMAITRE La Sécurité depuis 1974						
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.								
Symbols									
Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP   <u>sales@performance-brands.co.uk</u>   <u>www.performance-brands.co.uk</u>								