

Name	PB 203 Libertine Low	
Standard	EN ISO 20345:2011 S3 SRC	
Description	Black S3 Ladies Safety Shoe	
Weight	385 grams	
Colour	Black	

Sizes	3	4	5	6	7	8								
-------	---	---	---	---	---	---	--	--	--	--	--	--	--	--

Properties	<p>Upper – Breathable, Full Grain Super Soft Tumbled Leather. Inner Lining – Abrasion Resistant, Moisture Wicking Textile. Toe Cap – Polycarbonate Toe Cap Resistant to 200J. Midsole – Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit – Lightweight Dual Density Parabolic PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed – Moisture Wicking, Breathable, and Washable Footbed.</p>
------------	---

Areas of Application	<p>The Libertine Low is suitable for most industrial applications. Typical applications include warehousing, manufacturing and distribution. The textile midsole makes the boot ideal for driving as the shoe is very lightweight and flexible.</p>
----------------------	---

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	S3 SRC	
----------	--	--------	--

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk </p>
---------	---