


Code	PB248C-BLK	
Standard	EN ISO 20345:2011 S3 SRC	
Name / Description	Stockton – Parabolic Derby Boot	
Weight	620 grams	
Colour	Black	

Sizes	5	6	7	8	9	10	11	12	13				
-------	---	---	---	---	---	----	----	----	----	--	--	--	--

Properties	<p>Upper: Breathable, Full Grain Leather with PU Tongue and Collar with Scuff Cap. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Abrasion Resistant, Moisture Wicking Textile.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Textile Pierce Resistant Midsole – Min. 1100N.</p> <p>Sole Unit: Lightweight Parabolic Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p>
------------	--

Areas of Application	<p>The Stockton is suitable for most industrial applications. Typical applications include construction, warehousing, manufacturing and distribution. The textile midsole makes the boot ideal for driving in as the boot is very lightweight and flexible.</p>
----------------------	---

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	S3 SRC	 <p>LEMAITRE <i>La Sécurité depuis 1974</i></p>	
----------	--	--------	--	---

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk </p>
---------	---