

Code	PB249-BLK														
Standard	EN ISO 20345:2011 S3 SRC										S				
Name / Description	Riva Low B – Parabolic S3 Trainer									1.	A STATE OF THE STA				
Weight	550 grams														
Colour	Black														
Sizes	3 4	5	6	7	8	9	1	0	11	12	13				
Properties	Upper: Breathable, Leather with PU Tongue and Collar. (Leather 1.8-2.2mm) Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Steel Toe Cap Resistant to 200J. Midsole: Stainless Steel Midsole – Min. 1100N. Sole Unit: Lightweight PU Parabolic Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed.														
Areas of Application	The Riva Low is suitable for most industrial applications. Typical applications include warehousing, meter readers, manufacturing and distribution.														
Standard	EN ISO 20345:2011 C E Cat. 2	S	3 SRC		L	. E M La Sécu									
Care Instructions	polish. The s	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.													
Symbols															
Contact		Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk													