


Code	PB280C-BLK	
Standard	EN ISO 20345:2011 S3 SRC	
Name / Description	Stockton S – Parabolic Derby Boot	
Weight	630 grams	
Colour	Black	

Sizes	5	6	7	8	9	10	11	12	13				
-------	---	---	---	---	---	----	----	----	----	--	--	--	--

Properties	<p>Upper: Breathable, Full Grain Leather with PU Tongue and Collar with Scuff Cap. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Abrasion Resistant, Moisture Wicking Textile.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Stainless Steel Midsole – Min. 1100N.</p> <p>Sole Unit: Lightweight Parabolic Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p>
------------	---

Areas of Application	The Stockton S is suitable for most industrial applications. Typical applications include construction, warehousing, manufacturing and distribution.
----------------------	--

Standard	EN ISO 20345:2011  Cat. 2	S3 SRC	 LEMAITRE <i>La Sécurité depuis 1974</i>	
----------	---	--------	---	---

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	---

Symbols	
---------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk
---------	--