

Code	PB284-BLK	
Standard	EN ISO 20345:2011 S3 CI SRC ESD	
Name / Description	Super X Low – ESD Safety Trainer	
Weight	630 grams	
Colour	Black	

Sizes	3	4	5	6	7	8	9	10	11	12	13		
-------	---	---	---	---	---	---	---	----	----	----	----	--	--

Properties	<p>Upper: Breathable, Full Grain Nu-buck Leather with Textile Tongue and Collar. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Abrasion Resistant, Moisture Wicking Textile.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Textile Pierce Resistant Midsole – Min. 1100N.</p> <p>Sole Unit: Lightweight Dual Density Parabolic PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p> <p>Special Features: Abrasion Resistant Material across Toe and Vamp.</p>
------------	--

Areas of Application	<p>The Super X Low is suitable for any environments that specify an ESD requirement. Typical applications include electronic manufacturing, car production, chemical sites and pharmaceuticals. The extra protection across the toe area makes it perfect for jobs which involve kneeling as the leather is prevented from being worn away from the toe.</p>
----------------------	--

Standard	<p>EN ISO 20345:2011</p> <p></p> <p>Cat. 2</p>	<p>S3 CI SRC ESD</p>		
----------	---	----------------------	--	---

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd The Pavilion, Bowcliffe Hall, Bramham, Wetherby. LS23 6LP</p> <p> sales@performance-brands.co.uk www.performance-brands.co.uk</p>
---------	--