

| Code | PB321-BL | | | | | | | | | | |
|-------------------------|--|--------|---|---|----|----|-----|----|--------------|--|--|
| Standard | EN ISO 20345:2011 S3 SRC | | | | | | | D. | | | |
| Name / Description | Norris S3 Chukka Boot | | | | | | | | 1935 1935 | | |
| Weight | 610 grams | 1 | | | | | | | | | |
| Colour | Black | | | | | | | | | | |
| Sizes | 3 4 | 5 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | | |
| Properties | Upper: Genuine Breathable Leather. Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Steel Toe Cap Resistant to 200J. Midsole: Stainless Steel Midsole – Min. 1100N Sole Unit: Lightweight Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: EVA Footbed. | | | | | | | | | | |
| Areas of Application | The Norris S3 is suitable for most industrial applications. Typical applications include construction, warehousing, manufacturing and distribution. | | | | | | | | | | |
| Standard | EN ISO 20345:2011 C E Cat. 2 | S3 SRC | ; | S | AF | E. | TIX | K | | | |
| Care Instructions | For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced. | | | | | | | | | | |
| Symbols | | | | | | | | | | | |
| Contact | Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP <u>sales@performance-brands.co.uk</u> <u>www.performance-brands.co.uk</u> | | | | | | | | | | |