

| Code                  | PB335-BLK                     |         |         |        |        |          |        |         |       |     |    |  |  |  |
|-----------------------|-------------------------------|---------|---------|--------|--------|----------|--------|---------|-------|-----|----|--|--|--|
| Standard              | EN ISO 20345: 2011 S3 SRC     |         |         |        |        |          |        |         |       |     | k. |  |  |  |
| Name /<br>Description | Dune - Non Metal Safety Hiker |         |         |        |        |          |        |         |       |     |    |  |  |  |
| Weight                | 625 Grams                     |         |         |        |        |          |        |         |       |     |    |  |  |  |
| Colour                | Black                         |         |         |        |        |          |        |         |       |     |    |  |  |  |
| Sizes                 | 3                             | 4       | 5       | 6      | 7      | 8        | 9      | 10      | 11    | 12  | 13 |  |  |  |
|                       |                               |         |         |        |        |          |        |         |       |     |    |  |  |  |
|                       | Hnn                           | or: \// | ater Re | nellen | t Sued | le Snlit | l eath | er with | Scuff | Can |    |  |  |  |

**Properties** 

Toe Cap: Polycarbonate Safety Toe Cap - Resistant to 200J.

**Midsole:** High Tenacity Fabric <<0>> Penetration.

Sole Unit: Dual Density PU Soling System. Anti-Static, Shock Absorption, Heat Resistant to 120°C and SRC Slip Resistance. Studded Self Cleaning

Cleats.

Footbed: Moisture Wicking, Breathable Footbed.

Areas of **Application** 

The Dune is suitable for most industrial applications. Typical applications include indoor and outdoor activities, logistics, trade and manufacturing. The textile midsole makes the boot ideal for driving as the shoe is very lightweight and flexible.

100% Non-Metal.

**Standard** 

**EN ISO** 20345:2011

Cat. 2

S3 SRC



La Sécurité depuis 1974

Care **Instructions**  For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.

**Symbols** 

Contact

Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP | sales@performance-brands.co.uk | www.performance-brands.co.uk |