

FORSETI S3



Standard EN ISO 20345 : 2011



LEMAITRE


Safety since 1974



Sizes 35 to 49 Ref. FORSS30NR

Product Highlights

 Heavy duty boot available with men's and women's fit.

 2,0 mm thick high strength leather (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

• **Scuffcap TPU injected:** extreme resistance at the front.

• **Memory Foam Titan sole for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.

 • **Protective toe-cap:** composite HDFC.

 • **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAILIUM PU2D antistatic sole

• **4 mm studs** suitable for construction and heavy duty industry

• **Drainage channels for liquids and mud** to avoid any risk of aquaplaning

• **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs

• **Large bearing surface,** optimal stability

• **Arch support and heel cushioning:** MSD prevention

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority.



FORSETI S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with abrasion-resistant TPU scuffcap material
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard $\geq 0,32$)
forward heel slip: 0,31 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,20 (standard $\geq 0,18$)
forward heel slip: 0,17 (standard $\geq 0,13$)

VARIANT



Finn S3 SRC
FINNS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
550 g

Men fitting 40-49

Weight of one shoe size 42:
630 g

Gencods

35	3237154409350	43	3237154409435
36	3237154409367	44	3237154409442
37	3237154409374	45	3237154409459
38	3237154409381	46	3237154409466
39	3237154409398	47	3237154409473
40	3237154409404	48	3237154409480
41	3237154409411	49	3237154409497
42	3237154409428		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP		
S1		(A) (E) (Fo)
S1P		(A) (E) (Fo)
S2		(A) (E) (Fo) (Wru)
S3		(A) (E) (Fo) (Wru)

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

(A)	Anti-static footwear	(Ci)	Insulation against cold
(E)	Shock absorption at the heel	(Hi)	Insulation against heat
(Fo)	Fuel oil-resistant outsole	(Hro)	Outsole resistance to hot contact
(Wru)	Water penetration and water absorption resistant upper	(Wr)	Water resistant
	Electrostatic discharge	(An)	Ankle protection

SRA Slip-resistance on ceramic floors with detergent

SRB Slip-resistance on steel floors with glycerol

SRC = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0030
update: 04/12/20

Member of
SINAMAP

