

TYR S3 Vibram®



Standard EN ISO 20345 : 2011



LEMAITRE

Safety since 1974



Waterproof-breathable membrane lining

- 100% waterproof, breathable and anti-bacterial
- optimal ventilation
- improved comfort
- full upper-fitting

Size 35 to 49

Ref. TYRS30NR

Product Highlights



- Ranger available with men's and women's fit.



- **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

- **Scuffcap TPU injected:** extreme resistance at the front.

- **Memory Foam Titan sole for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.



- **Protective toe-cap:** composite HDFC.



- **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAIL VIBRAM® sole PU/antistatic nitrile rubber.



- **Exclusive technical sole developed in partnership with Vibram®.**

- **Semelle Outdoor** with excellent grip, Hi, HRO, adapted to difficult climatic conditions (hot and cold).

- **Excellent abrasion resistance.**

- **Raised heel (15 mm height)** for improved safety, especially on ladders.


USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, oil platform



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



TYR S3 Vibram®



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with abrasion-resistant TPU scuffcap material
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** imper-breathing membrane

Characteristics of the sole

- **Designation:** TRAIL VIBRAM®
- **Material:** polyurethane / antistatic nitrile rubber - Vibram®
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,43 (standard ≥ 0,32)
forward heel slip: 0,42 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
forward flat slip: 0,23 (standard ≥ 0,18)
forward heel slip: 0,19 (standard ≥ 0,13)

VARIANT



Brimir S3 SRC
BRIMS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
820 g

Men fitting 40-49

Weight of one shoe size 42:
900 g

Gencods

35	3237154406359	43	3237154406434
36	3237154406366	44	3237154406441
37	3237154406373	45	3237154406458
38	3237154406380	46	3237154406465
39	3237154406397	47	3237154406472
40	3237154406403	48	3237154406489
41	3237154406410	49	3237154406496
42	3237154406427		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP						
S1						
S1P						
S2						
S3						

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

	Anti-static footwear		Insulation against cold
	Shock absorption at the heel		Insulation against heat
	Fuel oil-resistant outsole		Outsole resistance to hot contact
	Water penetration and water absorption resistant upper		Water resistant
	Electrostatic discharge		Ankle protection

SRA Slip-resistance on ceramic floors with detergent

SRB Slip-resistance on steel floors with glycerol

SRC = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0025
updated: 04/12/20

Member of
SINAMAP

