

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/007/161/07/23/1095

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: LEMAITRE SECURITE

17, rue de Bitschhoffen LA WALCK 67350 VAL DE MODER

France

Description

PPE Type: a safety footwear

Product reference: MISTRAL S3S 40-49

Article code:

Construction and material of outsole: Injection PU interlayer / PU outsole

Pictures:



LEMAITRE 17, rue de Bitschhoffen MISTRAL S3S 42 23/03 S3S CI HI FO SC SR LG EN ISO 20345: 2022 Lot: 3237154531426 / 2303311

67350 VAL DE MODER - FRANCE

Reference standard: EN ISO 20345:2022

Classification: I Category: S3S CI HI FO SC SR LG

Size range: 40-49

Insert nature: Non Metallic **Toecap nature: Non Metallic**

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from JULY 2023 and the user instructions index V10 - 23/12/2022.

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this

Issued in Lyon by

Didier GUISADO

cofrac

Certification Manager





Date of first issue: 06 July 2023 End of validity date: 06 July 2028



www.ctcgroupe.com

cemarking@ctcgroupe.com

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective

Equipment and repealing the Directive 89/686/EEC.

LEMAITRE SECURITE

MANUFACTURER'S TECHNICAL FILE

Reference of the product: MISTRAL S3S 40-49

Article code:

Technical file index: 01

Last update: JULY 2023

IDENTIFICATION

Reference of the product: MISTRAL S3S 40-49

Article Code:

Technical file index: 01

Last update : JULY 2023

Manufacturer

LEMAITRE SECURITE

17, rue de Bitschhoffen LA WALCK 67350 VAL DE MODER

France

Tel: 388722880 Tel: 388722886

Factory

SOPIC

Rue de la mécanique - Zone industrielle de la Charguia - 2035 TUNIS

TUNISIE

Tel: +216 71 771 400 Fax: +216 71 771 477

FOOTWEAR DESCRIPTION

Footwear description

The classification of this footwear is I: Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear.

The design of this footwear is A: low shoe.

Visual description

General view:



Outsole view:



Reference of the mould: TRAILIUM

Range of sizes

40-49

Construction and material of outsole

Injection PU interlayer / PU outsole

Field of use

Construction and public works

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable		Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	\boxtimes		Standard
			\boxtimes	Instruction for use
				Marking
§1.4	Manufacturer's instructions and information is available		\boxtimes	Standard
			\boxtimes	Instruction for use
				Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	⊠	\boxtimes	Standard
			\boxtimes	Instruction for use
				Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.			Standard
				Instruction for use
			\boxtimes	Marking
			\boxtimes	Standard
§2.6	PPE is intended for use in potentially explosive atmospheres	\boxtimes	\boxtimes	Instruction for use
			\boxtimes	Marking
	PPE incorporating components which can be adjusted or removed by the user		\boxtimes	Standard
§2.9		\boxtimes	\boxtimes	Instruction for use
				Marking
	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	×	\boxtimes	Standard
§2.12			\boxtimes	Instruction for use
			\boxtimes	Marking
	Multi-risk PPE			Standard
§2.14			\boxtimes	Instruction for use
			\boxtimes	Marking
	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle		\boxtimes	Standard
§3.1.1			\boxtimes	Instruction for use
				Marking
	The PPE is intended to protect against falls due to slipping		\boxtimes	Standard
§3.1.2.1			\boxtimes	Instruction for use
			\boxtimes	Marking
	The PPE is intended to protect against static compression of a part of the body	⊠	\boxtimes	Standard
§3.2				Instruction for use
				Marking
	The PPE is intended to protect against mechanical injuries		\boxtimes	Standard
§3.3			\boxtimes	Instruction for use
			\boxtimes	Marking
§3.6	Protection against heat and/or fire	\boxtimes	\boxtimes	Standard
			\boxtimes	Instruction for use
			\boxtimes	Marking
§3.7	Protection against cold		\boxtimes	Standard
			\boxtimes	Instruction for use
			\boxtimes	Marking

FOOTWEAR CONSTITUTION

	Reference	Material	Color
	LS.C320	Buffalo Oiled Split Leather 2,0 mm (MOSS04)	Dark brown
	LS.C222	Buffalo Split Leather 2,0 mm PU coated (GROOVE01)	Black
	LS.C710	100% Polyamid - 300g/m²	Black
UPPER	LS.C770	Textile CORPET i s tr/h2/bo320tci) - 90%recycled PET 10%PL LINING - 650gr/mtq	Black
	LS.C610	Retro-reflective material - 1 Layer : Glass micro beads, 2 Layer : Special Reflective layer + resin coating, 3 Layer : Regenerated Lether - 950gr/m²	Grey
COLLAR	LS.C770	Textile CORPET i s tr/h2/bo320tci) - 90%recycled PET 10%PL LINING - 650gr/mtq	Black
TONGUE	LS.C770	Textile CORPET i s tr/h2/bo320tci) - 90%recycled PET 10%PL LINING - 650gr/mtq	Black
	LS.C530	100% PA MICROFIBER - 735gr/m ²	Black
VAMP LINING	LS.DE01	Textile 100% fibre polyester - 270 g/m²	Light grey
QUARTER LINING	LS.DQ21	Synthetic - 100% recycled PET - 540gr/mtl	Green
INSOLE	LS.P15	Textile - 50% recycled PET Fibers - 3950gr/m²	White
INSOCK	LS.PP20	65% recycled PU foam, 15% recycled polyester fabtric, 20% binder PU based -	Black
OUTSOLE	LS.SU51	PU mold TRAILIUM	Black/Green
TOE CAP	LS.BA20	Toecap 604 FIBER	
INSERT	LS.P15	Textile - 50% recycled PET Fibers - 3950gr/m²	White

PROTECTION SCOPE

Basic requirements

This product has been designed to be a safety footwear.

The applicable basic requirements are detailed in the following standard(s):

- EN ISO 20345:2022 Safety footwear

This product is a category II PPE.

At the date of the certificate, the product is in compliance with Annex XVII of the European REACh regulation (n° 1907/2006 and revisions)

Additional requirements

The claimed additional requirements are:

- Closed seat region
- Cleated outsole
- Perforation resistance (non-metallic insert type PS)
- Antistatic footwear
- Heat insulation
- Cold insulation
- Energy absorption of seat region
- Scuff cap abrasion
- Slip resistance (ceramic tile with glycerine)
- Upper: Water penetration and absorption of upper material
- Outsole : Fuel oil resistanceOutsole : Ladder grip system

MARKING - PACKAGING

Information marked on the footwear

- Logo of the Manufacturer
- * Logo **C €**
- * Manufacturer's name or commercial brand
- * Manufacturer's postal address
- * Manufacturer's type designation
- * Size
- * At least year and month of footwear manufacture
- * The number and year of the applicable specific standard(s)
- * The appropriate codes of marking according to the applicable requirements and additional protection and performance claimed

Marking example

 ϵ

LEMAITRE
17, rue de Bitschhoffen
67350 VAL DE MODER - FRANCE
MISTRAL S3S 42 23/03
S3S CI HI FO SC SR LG
EN ISO 20345 : 2022

Lot: 3237154531426 / 2303311

Method of marking on the footwear: Printed label inner tongue + engravings on the outsole

Packaging

Individual box and carton of 10 pairs

References of test reports performed in order to verify the compliance with the requirements of the technical rules:

Laboratory	References	Laboratory	References
CTC	D220920154_1	CTC	L220305232_1
CTC	L190815908_2	CTC	L220305234_1
CTC	L200202194_1	CTC	L220814651_1
CTC	L201220027_1	CTC	L220916099_1
CTC	L201220028_1	CTC	L220916107_1
CTC	L201220087_1	CTC	L220917827_1
CTC	L201220088_1	CTC	L230305876_1
CTC	L210101208_1	CTC	L230305890_1
CTC	L210509265_2	CTC	L230305893_1
CTC	L210917461_1	CTC	L230407169_1
CTC	L220202881_1	CTC	L230611385_1
CTC	L220303767_1	CTC	L230611406_1

MEANS OF CONTROL

We are ISO 9001 : 2015 certified, attached the certificate N° 1998/9390.11 issued by Afaq. Every week we do impact and compression tests.

At each delivery of anti-penetration inserts we do perforation tests.



PPE subject to ageing :

The design performance of this product can be affected by ageing. The peremption period is estimated at 60 months / 5 years when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear...).

Declaration of conformity:

The EU declaration of conformity can be accessed on the website: www.lemaitre-securite.com/reg