Code	**PB383C-BLK**
Standard	EN ISO 20345:2022+A1:2024 S3S SR LG CI FO SC HI HRO ESD
Name / Description	**Lemaitre Opal ESD PU/Rubber Safety Shoe**
Weight	**600 grams**
Colour	**Black**



Sizes	3	4	5	6	7	8	9	10	11	12	13		

Properties	**Upper:** Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.0mm). **Inner Lining:** Abrasion Resistant, Moisture Wicking Textile. **Toe Cap:** Lightweight Fibre Glass Toe Cap Resistant to 200J. **Midsole:** Textile Pierce Resistant Midsole – Min. 1100N. **Sole Unit:** Lightweight, Injected Dual Density PU/RU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SR rated Slip Resistance. **Footbed:** Moisture Wicking, Breathable and Washable Footbed.
Areas of Application	The PB383C-BLK is a PU/RU lightweight, non-metal shoe suitable for use in airports, security areas, or any environment where metal detectors are present. It is also suitable for use in a variety of industrial applications such as warehousing, engineering, distribution, manufacturing, security, transport and offices. It is suitable for any environments that specify an ESD requirement.

Standard	**EN ISO 20345:2022 +A1:2024** CE **Cat. 2**	**S3S SR LG CI FO SC HI HRO ESD**	LEMAITRE	

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
Symbols	
Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP | sales@performance-brands.co.uk | www.performance-brands.co.uk |