

Code	PB384C-BLK	
Standard	EN ISO 20345:2022 S3 S SR LG CI SC FO HRO	
Name / Description	Non-Metal Hiker	
Weight	650 grams	
Colour	Black	

Sizes	3	4	5	6	7	8	9	10	11	12	13		
-------	---	---	---	---	---	---	---	----	----	----	----	--	--

Properties	<p><b>Upper:</b> Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.0mm).</p> <p><b>Inner Lining:</b> Abrasion Resistant, Moisture Wicking Textile.</p> <p><b>Toe Cap:</b> Lightweight Fibre Glass Toe Cap Resistant to 200J.</p> <p><b>Midsole:</b> Textile Pierce Resistant Midsole – Min. 1100N.</p> <p><b>Sole Unit:</b> Lightweight, Injected Dual Density PU/RU Soling System with ESD Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p><b>Footbed:</b> Moisture Wicking, Breathable and Washable Footbed.</p>
------------	---

Areas of Application	<p>The PB384C-BLK is a PU/Rubber non-metal hiker suitable for use in airports, security areas, or any environment where metal detectors are present. It is also suitable for use in a variety of industrial applications such as warehousing, engineering, distribution, manufacturing, security, transport and offices. Also can be used in areas that need ESD Footwear</p>
----------------------	---

Standard	<p>EN ISO 20345:2022</p> <p></p> <p>Cat. 2</p>	<p>S3 S SR LG CI SC FO HRO ESD</p>	<p></p> <p><b>LEMAITRE</b></p> <p><i>La Sécurité depuis 1974</i></p>	
----------	---	--	--	--

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP</p> <p>  <a href="mailto:sales@performance-brands.co.uk">sales@performance-brands.co.uk</a>   <a href="http://www.performance-brands.co.uk">www.performance-brands.co.uk</a>  </p>
---------	---