

PERFORMANCE BRANDS

Code	PB408C-BLK	
Standard	EN ISO 20345:2022 S3S CI HI HRO LG FO SR	
Name / Description	Bedrock Non Metal Safety Hiker	
Weight	922 grams	
Colour	Black	

Sizes	3	4	5	6	7	8	9	10	11	12	13	14	
-------	---	---	---	---	---	---	---	----	----	----	----	----	--

Properties	Upper: R-180 full grain leather offering minimum 3 hour water protection. Lining: Abrasion resistant, moisture wicking textile. Toe Cap: HDFC Fibreglass Non Metal - Resistant to 200J Midsole: Textile pierce resistant - Min 1100N. Sole Unit: Tera-Lock™ Rubber Outsole. Lightweight performance rubber compound. Reinforced lug thickness at heel, ball and toe wear zones. Internal reinforced digging plate for added protection during tool work. Multi-directional lug geometry for grip in mud and uneven terrain. High abrasion resistance compound for extended outsole life. Anti-static and heat resistant to 300°C. Footbed: Moisture wicking, breathable and washable footbed with shock absorber.
------------	---

Areas of Application	The Bedrock Non-Metal Safety Hiker is a lightweight, durable boot designed for stability on uneven terrain. Featuring the advanced Tera-Lock™ outsole for superior grip and longevity, along with water-resistant leather and non-metal protection, it delivers reliable performance with enhanced ankle support and all-day comfort. Typical applications include construction, groundworks, utilities, and engineering.
----------------------	--

Standard	EN ISO 20345:2022  Cat. 2	S3S CI HI HRO LG FO SR	 LEMAITRE	
----------	---	---	--	--

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	--

Symbols	
---------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk
---------	---