

|                         |   |                                    |    |      |    |     |           | _       |            |  |  |  |  |
|-------------------------|---|------------------------------------|----|------|----|-----|-----------|---------|------------|--|--|--|--|
| Code                    | PB41-BLK  |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Standard                | EN ISO 20345:2011 S1 P SRC  |                                    |    |      |    |     |           |         |            |  | The state of the s |  |  |
| Name /<br>Description   | Tyson Low – Baseball Trainer  |                                    |    |      |    |     |           |         |            |  | 7  |  |  |
| Weight                  | 575 grams   |                                    |    |      |    |     |           |         | 1          |  |  |  |  |
| Colour                  | Black   |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Sizes                   | 6   | 7                                  | 8  | 9    | 10 | 11  | 12        |         |            |  |  |  |  |
| Properties              | Upper: Breathable, Suede/Textile Upper with Textile Tongue and Collar. Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Lightweight Aluminium Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Lightweight Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Areas of<br>Application | The Tyson Low is suitable for most industrial applications. Typical applications include manufacturing, warehousing and distribution. The textile midsole makes the trainer ideal for driving as it is very lightweight and flexible.   |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Standard                | 2034  | ISO<br>5:2011<br><b>C</b><br>at. 2 | S1 | P SR | c  | PRO | DDUCT PER | FORMANC | RF PASSION |  |  |  |  |
| Care<br>Instructions    | For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.   |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Symbols                 |   |                                    |    |      |    |     |           |         |            |  |  |  |  |
| Contact                 | Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP   sales@performance-brands.co.uk   www.performance-brands.co.uk   |                                    |    |      |    |     |           |         |            |  |  |  |  |