Code	**PB411C-BLK**
Standard	**EN ISO 20345:2022 S7S SR LG CI SC FO HRO**
Name / Description	**Strata Seal Waterproof Non Metal Safety Boot**
Weight	**941 grams**
Colour	**Black**



Sizes	3	4	5	6	7	8	9	10	11	12	13	14	

Properties	**Upper:** R-180 full grain leather offering minimum 3 hour water protection. **Lining:** Waterproof breathable and abrasion resistant, moisture wicking anti-bacterial textile. **Toe Cap:** HDFC Fibreglass Non Metal - Resistant to 200J **Midsole:** Textile pierce resistant - Min 1100N. **Sole Unit:** Tera-Lock™ Rubber Outsole. Lightweight performance rubber compound. Reinforced lug thickness at heel, ball and toe wear zones. Internal reinforced digging plate for added protection during tool work. Multi-directional lug geometry for grip in mud and uneven terrain. High abrasion resistance compound for extended outsole life. Anti-static and heat resistant to 300°C. **Footbed:** Moisture wicking, breathable and washable, with shock absorber.
Areas of Application	Lightweight, agile, and fully waterproof, the Strata Seal is built for demanding sites. Featuring the Tera-Lock™ outsole for grip and durability, water-resistant leather, a waterproof lining, and non-metal protection, it delivers reliable performance and all-day comfort. Typical applications include construction, groundworks, utilities, and engineering.

Standard	**EN ISO 20345:2022** CE **Cat. 2**	**S7S SR LG CI SC FO HRO**	LEMAITRE	

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
Symbols	

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP | sales@performance-brands.co.uk | www.performance-brands.co.uk |