

| Code | PB52-BLBU | | | | | | | | | | | | |
|-------------------------|--|---|---|---|---|---|---|----|----|----|----|--|------|
| Standard | EN ISO 20345:2011 S3 SRC | | | | | | | | | | | | |
| Name / Description | Tornado Low FG – Lightweight Non- Metal Trainer | | | | | | | | | | | | |
| Weight | 500 grams | | | | | | | | | | | | / in |
| Colour | Black/Blue | | | | | | | | | | | | |
| Sizes | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | | |
| Properties | Upper: Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.0mm). Inner Lining: B-dry Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Lightweight Fibre Glass Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Lightweight, Injected Dual Density PU/PU Soling System with Antistatic Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. | | | | | | | | | | | | |
| Areas of Application | The Tornado Low FG is a lightweight, non-metal trainer suitable for use in airports, security areas, or any environment where metal detectors are present. It is also suitable for use in a variety of industrial applications such as warehousing, distribution, manufacturing, security, transport and offices. | | | | | | | | | | | | |
| Standard | EN ISO 20345:2011 C E S3 SRC PRODUCT PERFORMANCE PASSION | | | | | | | | | | | | |
| Care Instructions | For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced. | | | | | | | | | | | | |
| Symbols | | | | | | | | | | | | | |
| Contact | Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk | | | | | | | | | | | | |